

Utility Noise Mitigation Plan



I Contact Information

Name of Responsible Party as defined in 15RCNY §28-109(a)
(Utility and/or Contractor and/or Sub)

Contact Phone Number _____

Work Schedule _____

DOT Permit (if needed) _____

Permits need not be posted for emergency response and for routine manhole work in accordance with NYC DOT and NYC DEP rules and regulations, unless work duration is undetermined or limited to one-shift/one-location, then fill in work location/schedule as listed in I above. Emergency work may commence and within 3 days, a permit shall be posted.

II Site-Specific Information

Hours of Work are to be in accordance with NYC DOT Permit Stipulations and/or NYC DOT Highway Rules. Additional mitigation techniques for receptors within 200 feet may be required by the DEP for hours between 10 PM and 7 AM during weekdays and 7PM and 7 AM during weekends.

Residents within 200 feet of a construction site shall be given notice when work is scheduled for longer than 3 days. Conspicuous posting of such information, or where necessary notification of building managers/owners, shall satisfy this requirement.

The owner/operator of sensitive receptors, adjacent to this site, shall be contacted when practicable to coordinate work to minimize impact on the property.

Vehicle engine idling at site shall be prevented in accordance with NYC Ad. Code §24-163.

All street plates at this site, shall be installed and properly secured in accordance with 34RCNY §2-11(10) (e)

All corrective action, at this site, shall be taken within 24 hours of notice by the DEP or its agent.

All rules of 28RCNY §106 apply.

III Construction Devices

This Plan certifies that all equipment indicated in this Mitigation Plan is maintained to operate in accordance with the manufacturer's operating specifications and has been equipped with appropriate manufacturer's noise reducing devices.

Check applicable boxes in next column:

When the specific devices listed in next column are utilized, the use of barriers is not required unless the Dept. of Environmental Protection receives complaints. NOTE: All devices must have manufacturer's noise reduction device installed and properly functioning.

- JACKHAMMERS (including chisel hammer attached to a vehicle like a backhoe)
 - Copco model TEX P90S with elongated muffler casing or bellows > 15 inches in length (or equivalent)
 - Chicago Pneumatic CP1240 with a model F-814004 muffler (or equivalent)
 - Other _____
- BACKHOES _____ method of mitigating device
- GENERATORS (Noise mitigation required – noise insulating fabric or other such techniques)
- COMPRESSORS (Noise mitigation required – noise insulating fabric or other such techniques)
- PUMPS (Noise mitigation required – noise insulating fabric or other such techniques)
- OTHER _____

IV Specialized Equipment: Circle applicable device

The vehicles listed below and other vehicles with internal combustion motors shall require noise mitigation measures as specified by the DEP, such as the use of noise-insulating material or other such techniques that do not interfere with engine operation. The location of receptors should be considered in the placement and use to minimize noise impact.

Roding Truck	Flusher Vac Truck
Pavement Core Drilling Truck	Vacuum Excavator Truck
_____ method of mitigating any of the above devices	

- BACKUP ALARMS (Required January 2008)
 - Preco Model 45AA (or equivalent)
 - Ecco Model 820 (or equivalent)
 - Preco Model 1048 (or equivalent)
 - Ecco Model SA907 (or equivalent)
 - Grote Model 73100 (or equivalent)
 - BBS-TEK Brigade Model BBS-92 (or equivalent)

Version _____ Date _____

You must use the latest version available. Please check the website:
<http://www.nyc.gov/html/dep/html/airnoise.html>